



EPOXY GROUT

HIGH PERFORMANCE EPOXY COLOURED GROUT



ECO FRIENDLY



COLOURS



EASE OF USE

DESCRIPTION

Davco Epoxy Grout is a dual component, general purpose, epoxy grout system, that is suitable for most types of ceramic and homogeneous tiles.

It is for interior use only and is ideal for application where grout width is between 2mm-15mm joint and Grout depth is from 3mm.

USES

Use for the grouting of ceramic and homogeneous wall and floor tiles in interior areas where higher grout standard is required.

Can be use in commercial areas that requires highly sanitized/hygienic environment such as dairies, breweries, food processing plants, hospitals, commercial laundries and kitchens.

Can be use in wet and humid areas such as indoor spas.

ADVANTAGES

- Resistant to water, stains, oil and chemical products including fat, bases, oils detergents, soaps, salts, mild acids and mild alkalis. and common solvents.
- Wide range of colours.
- Easy application. No on site mixing required.
- Lower shrinkage.
- Durable, long lasting and mould resistant.
- Environmentally friendly.

SURFACE PREPARATION

Allow the adhesive to set for at least 24 hours before grouting with Davco Epoxy Grout.

Ensure that grout width is at least 2mm.

Use a blower, vacuum cleaner or soft brush to ensure all tile joints are free from loose materials, dust, dirt and water prior to grouting with Davco Epoxy Grout.

Work the grout well into the tile joints using the recommended application gun.

Shape the joints with the recommended shaping tool.

Shave off the excess grout away with a cutter.

TECHNICAL DATA


Drying time: 4H (Surface dry)

Shore Type D hardness: 48


Bonding Strength: 1.8Mpa

Abrasive resistance: ≤ 0.06


Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.




1 Remove dirt and dust from the grout joints.



2 Use a caulking gun for application. Uncap the cartridge and fill the joint. (Do not use the first injected 30cm of Davco Epoxy Grout).



3 Use a stress ball to level Davco Epoxy Grout along grout joint.



4 Use a scraper to remove excess Davco Epoxy Grout.

BUILDING TRUST





EPOXY GROUT

PACKAGING

Davco Epoxy Grout is available in 400ml / kit Carton -30 kits per carton.

COVERAGE

The coverage varies with tile size and height and width of grout joints.

A 400ml kit will cover approx. 4.0m² of 150mm x 150mm x 9mm tiles incorporating 2mm grout joints.

Tile Size	2	2.5	3
800mm * 800mm	14m ² /kit	10m ² /kit	7m ² /kit
400mm * 800mm	10.5m ² /kit	7.5m ² /kit	5.5m ² /kit
600mm * 600mm	10.5m ² /kit	7.5m ² /kit	5.5m ² /kit
300mm * 600mm	7.5m ² /kit	5.5m ² /kit	4m ² /kit
200mm * 200mm	3.5m ² /kit	2.5m ² /kit	2m ² /kit
100mm * 100mm	2m ² /kit	1.5m ² /kit	1m ² /kit
50mm * 50mm	1m ² /kit	0.5m ² /kit	0.25m ² /kit



Davco Epoxy Grout
Application
Video

Scan here for
application video

SHELF LIFE

Up to 12 months in an unopened cartridge and when stored in a cool and dry place.

CLEANING

Clean tools and equipments with water before grout sets.

HEALTH & SAFETY

Davco Epoxy Grout, can act as an irritant to sensitive skins. Avoid skin contact with the grout. Wash well with soap and water. Get medical attention if irritation continues.

Davco Epoxy Grout is not suitable in areas where harsh chemicals are used.

Do not use acids or alkalis outside the range of pH 5-7 over Davco Epoxy Grout.

Good housekeeping practices must be observed at all times. Grouted floors and walls must be regularly cleaned and accidental spills must be flushed away immediately.

Do not allow pooling of water over the Davco Epoxy Grout while grout is still wet.

Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.parexgroup.com.sg

Sika (Singapore) Pte Ltd.

28 Tuas South Avenue 8 Singapore 637648

Tel: (65) 6861 0632 • Fax: (65) 6862 1172

Email: sales@sg.sika.com

Website: www.sika.com.sg

Online Store: davco-online.com.sg



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



Certificate GMS-C / GHG / 0002



Updated Jun 2019