



# ROCKFIL ECO

## PREMIUM GRADE, JOINT & INTERNAL SKIMMING COMPOUND



ECO FRIENDLY



LOW CARBON  
FOOTPRINT



EASE OF USE

### DESCRIPTION

Davco Rockfil ECO is a premium grade, polymer based joint and internal skimming compound that is available in paste form. Its unique cement free formulation and eco friendly packaging reduces the product's carbon foot print making it an environmentally friendly, all purpose joint compound.

### USES

Davco Rockfil ECO is ideal for smoothing the surfaces of masonry plastered wall prior to painting. It is also suitable for use on textured wall boards, laminated wall board, old plastered wall and gypsum wall board. After curing, Davco Rockfil ECO gives a smooth and hard surface which can be sanded down when required.

### ADVANTAGES

- Environmentally friendly and non toxic.
- Gives a hard surface which can be smoothed by sanding.
- Can feather edge.
- Quick drying with high bond strength.
- Excess product can be stored, reducing product waste.

### TECHNICAL DATA

Appearance	: White paste
Specific Gravity	: 1.68 ± 0.05
Pull-out strength (on plastered wall)	: 0.8 N/mm <sup>2</sup>

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.



Use as a joint compound



**PAREX**  
Building expertise, together





# ROCKFIL ECO

## SURFACE PREPARATION

Remove all dust, oil or traces of foreign materials. Dampen the dry concrete or plastered surface before application of Davco Rockfil ECO.

## APPLICATION

Fill in open space between panels with Davco Rockfil ECO using joint knife.

Apply thin skin coat over the joint to prevent the edge from wrinkling.

Joint reinforcing tape can be use over the seam. Allow to dry for 24 hours before application of second coat.

Apply finishing coat with trowel, use sand paper and hand sander to obtain a smooth surface.

## COVERAGE

Davco Rockfil ECO paste, can cover approximately 1.25m<sup>2</sup> per kg at 0.5mm thickness.

## PACKAGING

Davco Rockfil ECO is available, ready to use, in 25 kg pail and 5 kg pail.

## CLEANING

Use clean water to clean up excess Davco Rockfil ECO on tools.

## SHELF LIFE

Shelf life of product is up to 12 months when product is stored in a cool, dry place in the original unopened packaging.

## HEALTH & SAFETY

Davco Rockfil ECO is non hazardous. Avoid contact with skin or swallowing of product. In case of eye contact, wash with plenty of water. If irritation persists, seek immediate medical attention. Refer to safety data sheet.

### Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website [www.parexgroup.com.sg](http://www.parexgroup.com.sg)

## PAREXGROUP PTE LTD

28 TUAS SOUTH AVENUE 8, SINGAPORE 637648

TEL: (65) 6861 0632 FAX: (65) 6862 3915

EMAIL: SALES@PAREXGROUP.COM.SG

WEBSITE: WWW.PAREXGROUP.COM.SG

ONLINE STORE: DAVCO-ONLINE.COM.SG

ParexGroup, a French multi-national company with headquarters in Paris, is a leading manufacturer of speciality products for the construction industry with operations in more than 20 countries, and our 2700 people around the world are the cornerstone of our growing organization.

Updated TA56 Jun 2017



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ISO 14064 : 2006  
Certificate GMS-C / GHG / 0002

